

FleeceTape Information Sheet

Ideas for Usage

- For sealing damp proof membranes together where they join or overlap.
- For sealing floor to wall joints and around drains in wetrooms.
- For sound-deadening applications.
- For sealing cracks prior to plastering.
- For applications to prevent air leakage.



Key Benefits

- Good adhesion to a wide range of substrates.
- The product is highly conformable.
- Remains flexible throughout its service life.
- Easy and accurate to use with little waste and no mess.
- The fleece will accept paint, plaster, cement and adhesives.

Product Data

Packaging: 1mm x 115mm x 25m.

Colour: Black.

Shelf Life: 24 months when stored flat in original packaging in cool, dry conditions.

Application Temperature Range: 5°C to 40°C

Description

FleeceBand is a butyl tape laminated with a non-woven polyester fleece.

Directions for use:

Surface Preparation:

- All surfaces should be clean, dry and free from frost, grease and loose materials.
- When cleaning contaminated substrates, we recommend that propan-2-ol (IPA) is used and allowed to dry prior to the application of the butyl tape.
- When applying the tape to porous or friable surfaces, it is recommended that the surface be treated with a suitable primer, such as an exterior grade PVA, to seal and stabilise the surface.

Application:

- Remove the release paper and apply the tape to the substrates to be joined.
- Take care to avoid rucks in the tape. Roll the tape with a small roller to ensure good adhesion along the whole length of the rope.

FleeceTape Information Sheet

Performance			
	Unit	Nominal Value	Test Method
Dynamic Shear Adhesion	N/cm ²	12	H15
90° Peel Adhesion	N/cm	8	H48
180° Peel Adhesion	N/cm	9	H41
Specific Gravity	g/cm ³	1.6	H6
Moisture Vapour Transmission Rate	g/m ² /24hr/mm	0.18	ISO9932 / BS ISO 15106
Service Temperature Range	°C	-40 to +90	

Important Information

SkilledBuild is committed to development and supply of quality products and may substitute or change product branding or specification or technical data without notice. Always check for latest information.

All information provided is based on practical tests & published data and is intended to guide a competent DIY user or contractor in the typical use of products for minor works but is without guarantee. If a failure of the works will be costly to repair or hazardous then design & execution must be undertaken by competent persons. Further advice should be sought from a suitably qualified advisor. Skilled Build may be able to answer simple product enquiries.

Since application and working and user competence is beyond our control, no liability of the supplier can be derived from the contents of information sheets or other general information provided. Any statements made beyond the contents of SkilledBuild's website or product labels must be confirmed in writing by the supplier.