

SKILLEDBUILD ToughBond+ PVA Wood Glue **Safety Data Sheet**

(17th April 2012)

Product Identification

Trade Name: ToughBond+ PVA Wood Glue

Description: Wood adhesive.

Hazardous Ingredients

Classification Concentration Component **EINECS**

Hazard Identification

No significant hazard.

Emergency and First Aid

After Eye Contact: Rinse immediately with plenty of water for 15 minutes holding the eyelids

After Skin Contact: Wash off immediately with plenty of soap and water. Remove

contaminated clothing.

After Ingestion: DO NOT INDUCE VOMITING.

After Inhalation: Move the exposed person to fresh air.

Exposure Control/Personal Protection

Engineering Controls: Ensure adequate ventilation of the working area.

Personal Protection: Wear protective clothing.

Eye/Face Protection: In case of splashing, wear: Approved safety goggles.

Toxicological Information

No data is available on this product.

Ecological Information

The preparation has not been tested but, it is miscible in water, and is thus likely to be transported considerable distances if allowed to ingress into water. The product is poorly biodegradable but not susceptible to bioaccumulation. The biological oxygen demand of other components may be harmful to aquatic organisms (R51/53).

Accidental Release Measures

Personal Precautions: Ensure adequate ventilation of the working area.

Environmental Precautions: Do not allow the product to enter drains. Prevent further spillage if safe. **Containment and Clean up Methods**: Absorb with inert, absorbent material. Sweep up. Transfer to suitable,

labelled container for disposal. Clean spillage area thoroughly with plenty

of water.



ToughBond+ PVA Wood Glue Safety Data Sheet

(17th April 2012) (vers

Stability and Reactivity

Stability: Stable under normal conditions.

Fire Fighting Measures

Extinguishing Media: Use extinguishing media appropriate to the surrounding fire conditions.

Special Hazards: Burning produces irritating, toxic and obnoxious fumes. **Advice for Firefighters:** Wear suitable respiratory equipment when necessary.

Handling and Storage

Handling: Avoid contact with eyes and skin. Ensure adequate ventilation of the working

area. Adopt best Manual Handling considerations when handling, carrying

and dispensing.

Storage: Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store

in correctly labelled containers.

Physical and Chemical Properties:

Appearance: White liquid.

Odour: Characteristic.

Freezing Point: 0 °C.

pH: 2.8 – 3.6 **Boiling Point**: 100 °C.

Relative Density: 1.1 (Water =1 @20 °C)

Solubility: Miscible in water.

Waste Disposal

Dispose of in compliance with all local and national regulations. Do NOT reuse empty containers.

Transport Information

This product is not classified as dangerous for carriage.

Regulatory Information

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.



ToughBond+ PVA Wood Glue Safety Data Sheet

(17th April 2012)

(version 1)

Disclaimer

The information in this document is offered for general health and safety guidance only and is not intended to be a definitive source of advice, nor does it constitute a risk assessment, for which the user is responsible. All information provided in this document is believed to be accurate to the best of our knowledge. Users of the products referred to should observe the recommendations, conditions and instructions relating to any relevant product label, usage information, consent or approval in force at the time. Further and more specific information may be obtained from the supplier on request (small fee may be required for this service). This company shall not be held liable for any damage resulting from handling or from contact with the above product.