



(17th April 2012)

(version 1)

Product Identification

Trade Name:Polyester Styrene Free Resin. **Description:**A chemical anchoring application.

Hazardous Ingredients

Component	EINECS	CAS Number	CHIP Classification	Percent
Vinyl Toluene	246-562-2	25013-15-4	R10; Xn: R20; Xi: R36/37/38	10-20%
Dibenzoyl Peroxide	202-327-6	94-35-0	[E] R3; [O] R7; [Xi] R36; [Sens.] R43	<1%

Hazard Identification

Hazard: No significant hazard.

PBT: This substance is not identified as a PBT substance.

First Aid Measures

After Eye Contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

After Skin Contact: Remove all contaminated clothes and footwear immediately unless

stuck to skin. Wash immediately with soap and water. Consult a

doctor.

After Ingestion: If conscious, give half a litre of water to drink immediately. Do not

induce vomiting. Consult a doctor.

After Inhalation: Move to fresh air in case of accidental inhalation of vapours.

Consult a doctor.

Most Important Symptoms And Effects

Skin Contact: There may be irritation and redness at the site of contact.

Eye Contact: There may be irritation and redness.

Ingestion:Harmful if swallowed.Inhalation:Harmful by inhalation.

Delayed/Immediate Effects: Not applicable.

Ecological Information

Ecotoxicity Values:

Persistence:

Mobility in Soil:

Bio-Accumulative:

Not applicable.

No data available.

Insoluble in water.

No data available.

PBT Identification: This substance is not identified as a PBT substance.

Other Adverse Effects: No data available.



(17th April 2012) (version 1)

Toxicological Information

Mobility: Insoluble in water.

Inhalation: Harmful by inhalation.

Skin Contact: There may be irritation and redness at the site of contact.

Eye Contact: There may be irritation and redness.

Ingestion: Harmful if swallowed.

Exposure Control/Personal Protection

Workplace Exposure Limits: Not applicable.

Engineering Measures: Ensure there is sufficient ventilation of the area. Ensure all

engineering measures mentioned in the Handling and Storage

section are in place.

Respiratory Protection: Breathing protection is required in inadequately ventilated places.

Hand Protection:Protective gloves.Skin Protection:Protective clothing.Eye Protection:Safety glasses.

Environmental: Ensure all engineering measures mentioned in the Handling Storage

section are in place.

Physical and Chemical Properties:

Physical Form: Paste.

Colour: Various.

Odour: Sweet smelling.

Oxidising: Oxidising (by EC criteria).

Solubility in Water: Insoluble.

Flammability Limits %: lower: 380 Upper: 575.

Flash Point °C: 55
Relative Density: 1.56
VOC g/l: 211.6

Stability and Reactivity

Reactivity: Stable under recommended transport or storage conditions.

Chemical Stability: Stable under normal conditions. May polymerise on heating

Conditions to Avoid: Heat. Sources of ignition. Direct sunlight.

Materials to Avoid: Reducing agents. Amines. Acids. Alkalis. Heavy Metal Compounds.

Hazardous Reactions: Hazardous reactions will not occur under normal transport or

storage conditions.

Hazardous Decomposition Products: If exposed to high temperatures it will emit hazardous fumes and

smoke.





(17th April 2012)

(version 1)

Accidental Release Measures

Environmental Precautions: Do not discharge into drains or rivers.

Clean-Up Procedures: Transfer to a suitable container. Wash the area with water.

Handling and Storage

Handling Requirements: Keep away from heat and sources of ignition.

Storage Conditions: Ensure lighting and electrical equipment are not a source of ignition.

Store in cool, well ventilated area.

Suitable Packaging: Must only be kept in original packaging.

Specific End Use(s): Building and construction work (SU19).

Waste Disposal

Disposal Operations: Transfer to a suitable container and arrange for collection by

specialised disposal company. Small quantities of the product can be mixed and allowed to cure, then can be disposed as solid waste.

Waste Code Number: 08 04 12

Disposal of Packaging: Dispose of in a regulated landfill site or other method for hazardous

or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional

or national regulations regarding disposal.

Fire Fighting Measures

Extinguishing Media: Suitable extinguishing media for the surrounding fire should be

used. Dry chemical powder. Carbon Dioxide. Do not use halons.

Exposure Hazards: Sealed, heated containers can pressurise leading to explosion. In

combustion emits toxic fumes.

Advice for fire-fighters: Wear self-contained breathing apparatus.

Regulatory Information

Labelling: No significant hazard.

Safety Phrases: S2: Keep out of the reach of children S24: Avoid contact with skin

S37: Wear suitable gloves

Precautionary Phrases: Contains dibenzoyl peroxide. May produce an allergic reaction.

Safety, Health and Environment: Not applicable.

Chemical Safety Assessment: A chemical safety assessment has not been carried out for the

substance or the mixture by the supplier.





(17th April 2012)

(version 1)

Transport Information

Transport Class: This product does not have classification for transport.

Other Information

Other Information: This safety data sheet is prepared in accordance with Commission

Regulation (EU) No 453/2010.

Active Oxygen Content of Catalyst Component 0.99%.

Phrases Used in s.2 and 3: R10: Flammable. R20: Harmful by inhalation. R36/37/38: Irritating

to eyes, respiratory system and skin.

Disclaimer

The information in this document is offered for general health and safety guidance only and is not intended to be a definitive source of advice, nor does it constitute a risk assessment, for which the user is responsible. All information provided in this document is believed to be accurate to the best of our knowledge. Users of the products referred to should observe the recommendations, conditions and instructions relating to any relevant product label, usage information, consent or approval in force at the time. Further and more specific information may be obtained from the supplier on request (small fee may be required for this service). This company shall not be held liable for any damage resulting from handling or from contact with the above product.