

THE GIST SILICONE SEALANT Information Sheet

Areas of Use

- Sanitary applications
- Window frames
- Ducting
- High temperature applications
- Natural stone
- Metals
- Mirrors
- Granite
- Travertine
- Marble
- Stone
- PVCu
- Concrete
- Plaster
- VSG Glass

Key Benefits

- Developed for most sealing applications.
- Excellent adhesion properties.
- Non-staining.
- Resistant to UV.
- Mould resistant for up to 10 years.
- Non-shrinking.
- Can be used with temperatures up to 220°C.
- Shower in 1 hour.
- It will not bleed into porous stone.

Product Data

Packaging: 310ml plastic cartridge

Shelf Life: Minimum 12 months in unopened cartridges.

Storage: Store in cool, dry conditions.



Description

If you want a silicone sealant that does it all then you need 'THE GIST'. This all-in-one silicone bonds to numerous materials, including concrete, marble, granite, metal, glass, mirrors, PVCu and even natural or porous stone. THE GIST also contains a fungicide so it prevents mould growth for up to 10 years in kitchens, bathrooms and high humidity areas. What's more it doesn't stain, can be used with temperatures up to 220°C and is resistant to UV. All in all, it really is a silicone sealant designed to replace all others.

Directions for use:

Preparation:

- Ensure surfaces are sound, clean, dust free and dry prior to application.
- If sealing deep joints use foam backer rods to optimise joint design.
- Remove any old sealant.

Application:

- Apply using a standard sealant gun.
- Cut the top of the cartridge, screw on nozzle and cut to an angle of 45°C at desired sealant width.
- Tool the sealant using an appropriate tooling aid within 10 minutes of application – do not use a wetted finger.

THE GIST SILICONE SEALANT Information Sheet



For Bath Surrounds

- ½ fill bath with water to allow sealant to be applied at joint midpoint.
- If necessary masking tape may be applied.
- If large gaps are to be filled, polythene foam, rod or tape should be used to provide support and minimise sealant wastage.
- Tool down within 5 minutes using a wet spatula. Any trims should be bedded into the silicone within 5 minutes.

Disposal:

- Do not leave empty containers where residue could be harmful to children, animals or the environment.
- Replace lids and remove any containers to a central disposal point in accordance with local regulations.

Limitations:

- Not suitable for aquaria and permanent immersion i.e. swimming pools.

Health and Safety:

- Contains Butanone Oxime – may cause an allergic reaction.
- Keep out of reach of children.
- Avoid eye contact and prolonged contact with skin.
- Always follow manufacturer's recommendations when using this product.
- It is the user's responsibility to determine suitability.
- Safety Data sheet available online for more information.

Important Information

SkilledBuild is committed to development and supply of quality products and may substitute or change product branding or specification or technical data without notice. Always check for latest information.

All information provided is based on practical tests & published data and is intended to guide a competent DIY user or contractor in the typical use of products for minor works but is without guarantee. If a failure of the works will be costly to repair or hazardous then design & execution must be undertaken by competent persons. Further advice should be sort from a suitably qualified advisor. Skilled Build may be able to answer simple product enquiries.

Since application and working and user competence is beyond our control, no liability of the supplier can be derived from the contents of information sheets or other general information provided. Any statements made beyond the contents of SkilledBuild's website or product labels must be confirmed in writing by the supplier.