

Decorators Caulk Information Sheet



Description

An easy to apply, quick drying, interior decorators filler that can be smoothed and painted over within 1-2 hours of application.

SKILLED BUILD DECORATORS CAULK has good adhesion to most building materials and can be used to seal door and wooden window frames as well as interior sealing of skirting boards and polystyrene coving. It is also suitable for sealing interior partition joints around fitted furniture and for repairing small cracks and joints with no movement in plaster and wood.

Directions for use:

Preparation:

- All surfaces must be clean, dry, sound and free from dust, oil or any other contaminants that may hinder adhesion.
- If necessary, in addition to mechanical means, cleaning with a solvent such as acetone is recommended for degreasing.

Priming:

- SKILLED BUILD DECORATORS CAULK does not require a primer on most common construction surfaces. However, in some cases it may be necessary to prime concrete or other surfaces for optimum adhesion. To determine whether a primer is required a sample should be tested.

Application:

- Apply using a standard sealant gun.
- Cut tip from cartridge, be careful not to damage the screw thread. Cut the nozzle at an angle of 45 degrees to an opening slightly larger than the gap to be sealed, and fix to cartridge.
- Smooth down within 10 minutes using a slightly wetted spatula or sponge. Do not tool down after the skin has started to form.
- Do not saturate the surface with water as this will delay the curing process.

Areas of Use

- Wood .
- Light fittings.
- Stair risings.
- Plaster.
- Brick.
- Concrete.
- Plasterboard.

Key Benefits

- Reduces corrosion and decay.
- Resistant to most salt solutions, some dilute acids and alkalis, water and alcohol.
- Can be painted over 1-2 hours after application.

SILICONE SEALANT REMOVER Information Sheet

Product Data

Appearance: Black liquid.

Packaging: 5l

Limitations: Not suitable when applied at temperatures below 5°C.

Shelf Life: Minimum of 5 years under good storage conditions in original unopened containers.

Storage: Store under cover away from sources of heat and ignition. Keep containers sealed when not in use.

Coverage: Approximately 4-6m² per 1 litre (dependant on service conditions).

Service Temperature Limits: -20°C to 50°C depending on service conditions.

Application Temperature Limits: Normally 5°C to 40°C and free from ice/water.

Important Information

SkilledBuild is committed to development and supply of quality products and may substitute or change product branding or specification or technical data without notice. Always check for latest information.

All information provided is based on practical tests & published data and is intended to guide a competent DIY user or contractor in the typical use of products for minor works but is without guarantee. If a failure of the works will be costly to repair or hazardous then design & execution must be undertaken by competent persons. Further advice should be sought from a suitably qualified advisor. Skilled Build may be able to answer simple product enquiries.

Since application and working and user competence is beyond our control, no liability of the supplier can be derived from the contents of information sheets or other general information provided. Any statements made beyond the contents of SkilledBuild's website or product labels must be confirmed in writing by the supplier.

- SKILLED BUILD DECORATORS CAULK can be over painted with emulsion paint as soon as a skin forms, approximately after 1 hour. For oil based paints, allow to dry completely for 24 – 48 hours before over painting.
- Remove excess product with a damp cloth.

Safety:

- **Flammable:** Keep away from sources of ignition including pilot lights and sparks. Take precautionary measures against static discharge. Keep containers tightly closed when not in use. DO NOT SMOKE. If used in an enclosed space ensure thorough ventilation of the area (using flame proof mechanical blowers if necessary) to avoid any accumulation of vapour until the product has dried. In case of fire use dry powder, carbon dioxide, foam, sand or earth. Never use water. As this may spread the fire. **Note:** Electric motors, light/power switches and steel tools may generate sparks sufficient to ignite the product or it's vapour, resulting in an explosion and/or fire. °C
- **Skin Contact:** Contains solvents that cause de-fatting of the skin and, in extreme circumstances, dermatitis. Avoid contact by careful working and use of a barrier cream on hands, arms and other exposed areas or wear gloves. Remove skin contamination immediately with a proprietary hand cleaner and wash with soap and water.
- **Eye Contact:** Avoid contact. Could have an irritating effect in the event of accidental contact, wash eyes immediately with clean water for 15 minutes and obtain medical attention.
- **Inhalation:** Contains solvent. Stand upwind of the work to avoid inhalation. Switch off all working ventilation inlets prior to using this material; leave covered until there is no odour of the solvent in the vicinity. In the event of discomfort as a result of inhalation move person to fresh air. If discomfort persists seek medical advice.
- **Oral Ingestion:** With proper handling this should not occur. The possibility can be minimised by not consuming food in the working environment and by washing hands thoroughly before eating, drinking or smoking.
- **Spillage:** Spilt material should be mopped up immediately with an inert absorbent material, such as sand, and disposed of in accordance with regulations.