

Patching Plaster Information Sheet

Areas of Use

- Plaster.
- Plasterboard.
- Wood.
- Brick .
- Stone.
- Most other Building Materials.

Benefits

- Shrink and crack resistant.
- Easy to mix and simple to use.
- Has excellent adhesive properties, keeping the plaster firmly in place whilst drying.

Product Data

Packaging: 1.5kilo

Storage: Store in a dry place keeping sachet and box closed.

Important Information

SkilledBuild is committed to development and supply of quality products and may substitute or change product branding or specification or technical data without notice. Always check for latest information.

All information provided is based on practical tests & published data and is intended to guide a competent DIY user or contractor in the typical use of products for minor works but is without guarantee. If a failure of the works will be costly to repair or hazardous then design & execution must be undertaken by competent persons. Further advice should be sort from a suitably qualified advisor. Skilled Build may be able to answer simple product enquiries.

Since application and working and user competence is beyond our control, no liability of the supplier can be derived from the contents of information sheets or other general information provided. Any statements made beyond the contents of SkilledBuild's website or product labels must be confirmed in writing by the supplier.



Description

SkilledBuild Patching Plaster gives a smooth surface, perfect for overpainting or wallpapering. It can be used to fill holes and cracks in walls, ceilings and around door frames and skirting boards.

Directions for use:

Preparation:

- Mix SkilledBuild Patching Plaster with cold water to a thick consistency. Approximately 2 parts plaster to one part cold water.
- Always mix plaster in a clean container.

Application:

- Brush out loose material and dust from the crack or hole to be filled.
- Apply plaster with trowel or knife and press firmly into cavity.
- When repairing deep holes apply in layers allowing each layer to dry before applying the next.
- The plaster stays workable for approximately 1.5 to 2 hours after mixing.
- SkilledBuild Patching Plaster dries white and can be over painted or papered without priming.

Cleaning

- All tools and mixing bowls should be cleaned with warm water before plaster sets.
- Dirty tools can shorten setting times.